



Date of issue : 05/01/2005

Last. mod. date : 16/03/2009

Product code**01228 ULTRACRYSTALLINE Perm/Perm PP CLEAR ASP 8A permanent PET 30****Description**

Optically clear double side tape to be used where ultra transparency is required.

Not printable.

Permanent adhesive with high adhesion and shear at high temperature too. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

For applications on windows, glass, clear boards, etc.

Technical data**FACE MATERIAL**

| | |
|-------------------|--------------------------|
| Type | Top coated polypropylene |
| Colour and Finish | Clear, gloss |
| Weight | 27g/m ² |
| Thickness | 30μ |

ADHESIVE

| | |
|------------------|-----------------------|
| Reference | AP 906 |
| Type | Acrylic permanent |
| Min. Appl. Temp. | +10°C |
| Service Temp. | -40°C/+140°C |
| Shear | Very high |
| Tack FTM9 | 15N/inch ² |
| FinAdh FTM2 | 7N/inch |

RELEASE BACKING

| | |
|-------------------|------------------------------|
| Type | 1 side siliconised polyester |
| Colour and Finish | Clear |
| Weight | 46g/m ² |
| Thickness | 30μ |
| Transparency | >95% |

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrana's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrana can give no guarantee beyond the information given in the data sheet.