

GRAPHICS - RI-MARK

 Issue date : 05/01/2005
 Date last modification : 11/07/2017

FLUORESCENT SERIES ASP27 PERMANENT WHITE WK140

Face Material

Self-adhesive material for plotter. Fluorescent vinyl. Liner that offers superior cuttability with conventional die-cutting and computer signmaking systems.

Type	Fluorescent vinyl	
Colour and Finish	5 colours available	
Weight	125 g/m ² ±10%	ISO-536
Thickness	100 µ ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive white pigmented featuring medium cohesion. The excellent water resistance allows wet application of the material.

Reference	ASP27 white	
Type	Acrylic permanent	
Min. Appl. Temp.	+10°C	
Service Temp.	-20°C/+120°C	
Shear	High	
Tack	High N/inch ²	
Final Adhesion	Medium N/inch	

Liner

Type	One side siliconised clay coated Kraft	
Colour and Finish	White	
Weight	140 g/m ² ±10%	PP-032 - ISO 536
Thickness	150 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

Applications

Short term eye-catching colours for exterior safety, promotional and high visibility applications, such as slogans and prices. **6 months outdoor durability. Durability is given in good faith based on simulated weathering tests and real life vertical exposure in non-extreme mid-European conditions.**

Printing Methods

Not printable.
 Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

