



Date of issue : 05/01/2005

Last. mod. date : 27/11/2009

**Product code****01346 RI-121/200 FLOOR TALKERS EMBOSSED ASP8A permanent WG 90****Description**

Embossed, scuff resistant, non-slip overlaminating film for retail floor graphics.

Not printable.

Permanent adhesive with high adhesion and shear at high temperatures. Suitable for outdoor applications. Not suitable for apolar substrates (PE,PP).

Floor graphic overlaminating film suitable for applications requiring a hard-wearing 'scuff resistant' film. This product has been tested in accordance with the guidelines recommended by the UK Slip Resistance Group, "The Assessment of Floor Slip Resistance" - Issue 3, 2005. Please ask for further details.

**Technical data****FACE MATERIAL**

Type	Plasticised vinyl film
Colour and Finish	Clear embossed
Weight	260g/m <sup>2</sup>
Thickness	200μ

**ADHESIVE**

Reference	ASP 8A permanent
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-40°C/+140°C
Shear	Very high
Tack FTM9	15N/inch <sup>2</sup>
FinAdh FTM2	7N/inch

**RELEASE BACKING**

Type	1 side siliconised glassine
Colour and Finish	White
Weight	90g/m <sup>2</sup>
Thickness	77μ
Transparency	32%

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.